

VISONA

DEMOUNTABLE ACOUSTICAL CEILING

- ✓ Directional ceiling look
- ✓ Light fixtures moved without demounting tiles
- ✓ Easily adapted to changing room purposes
- ✓ Sustainable

FEATURES




- T-grid ceiling
- Rectangular ceiling tiles
- Installation in double T-grid
- Installation from below the T-grid

SUSTAINABLE PRODUCT:

- Made of gypsum
- Safe material
- 100% recyclable
- Improved indoor climate
- Repaintable without loss of acoustics



PRODUCT SPECIFICS

EDGE DESIGN	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>EDGE E lengthwise Lay-in tile in recessed grid lengthwise</p> </div> <div style="text-align: center;">  <p>EDGE B crosswise No cross tees between tiles crosswise</p> </div> </div>				
PERFORATION DESIGN Also available without perforations (Regula)					
PERFORATION MEASURES	<p style="text-align: center;">TANGENT Obround 4 x 14 mm c/c 10/20 mm</p>				
PERFORATION %	<p style="text-align: center;">21.3%</p>				
NRC, @ 200mm, no mineral wool	<p style="text-align: center;">0.75</p>				
NRC, @ 200mm, 50mm mineral wool	<p style="text-align: center;">0.90</p>				
ALPHA-W, @ 200mm, no mineral wool	<p style="text-align: center;">0.80</p>				
ALPHA-W, @ 200mm, 50mm mineral wool	<p style="text-align: center;">0.90</p>				
LIGHT REFLECTION	<p style="text-align: center;">70.9%</p>				
TILE WEIGHT, kg/m²	<p style="text-align: center;">7.6 kg/m²</p>				
SIZES, mm	<table style="width: 100%; border: none;"> <tr> <td style="border: none; padding-right: 10px;">Standard</td> <td style="border: none; text-align: center;">400 x 1200 x 12.5</td> </tr> <tr> <td style="border: none; padding-right: 10px;">Other options</td> <td style="border: none; text-align: center;">300-400 x 600-2400 x 12.5</td> </tr> </table>	Standard	400 x 1200 x 12.5	Other options	300-400 x 600-2400 x 12.5
Standard	400 x 1200 x 12.5				
Other options	300-400 x 600-2400 x 12.5				
SURFACE TREATMENT	<p style="text-align: center;">Front: White acrylic paint, RAL 9003, gloss 5. Back: Acoustic felt backing. Available in other colours on request.</p> <p style="text-align: center;">Also available with hygienic Medifend surface paint on request. Medifend has antibacterial and fungistatic effect. Tested in accordance with DIN ISO 846, method B and B'.</p>				
SYSTEM COMPONENTS	<p style="text-align: center;">1) Gypsum ceiling tile, 2) T24/38 main runner, 3) Spacer bar, 4) DG clips, 5) Hangers</p>				
CERTIFICATES	<p style="text-align: center;">1) Environmental product declaration, 2) FDES – life cycle analysis, 3) Danish Indoor Climate Labelling, 4) ISO 16000-9 Emission of VOCs, 5) UL-listed in accordance to R26164</p>				

FIRE RATING

A2-s1, d0

AIR QUALITY

Indoor value: 10 days
Particle emission: LOW
Active air purification with
Cleaneo technology

PRODUCT PERFORMANCE

AMBIENT CONDITIONS

Can withstand:
- constant RH 70% and 25°C
- ambient temperatures of up to 50°C.

LOAD-BEARING CAPACITY

Up to 1 kg pr. tile (at max. 2mm deflection)

ROBUSTNESS

Glass fibre reinforced gypsum. High pressure resistance. Highly stable ceiling ensured by tile density.